

LT625 DAY CAB



Configuration: 125" BBC
Engine: International® S13, International® A26 or Cummins® X15

International® LT® Series shown with International® S13



- ▶ Regional or Local Haul Applications
- ▶ Pick up and Delivery
- ▶ Van, Flatbed, or Specialty Haul
- ▶ Fleet or Owner Operator

The International® LT® Series Day Cab offers the features, performance and durability that can impact your bottom-line year after year and mile after mile. Your operational savings is now further enhanced by the availability of the all-new International® S13 Integrated Powertrain. The LT Series also benefits drivers like never before with an interior that was designed to optimize visibility, maneuverability, ingress/egress and dozens of other smart features to keep drivers comfortable and in control throughout the day.





KEY FEATURES:

- ▶ Now offered with the revolutionary International® S13 Integrated Powertrain featuring a sleek and refined grille design
- ▶ Aerodynamic and Powertrain Packages available to maximize fuel efficiency
- ▶ Standard Bendix® Wingman® Fusion™ Collision Mitigation System
- ▶ Standard Predictive Cruise Control for greater fuel efficiency and lower operating costs
- ▶ Premium gauge cluster designed with driver input is customizable with virtual gauges
- ▶ The dash is designed for the driver with controls and switch placement optimized by frequency of use
- ▶ Easy-access column-mounted shifter integrated with engine braking helps keep hands on the wheel



TWO WAYS TO RULE THE ROAD.



International® LT® Series shown with S13 Integrated Powertrain

International® LT® Series shown with A26 or X15 engine

125" BBC SET-BACK FRONT AXLE

GVW

- ▶ 32,000 - 60,000 lbs.

BBC/BA

- ▶ 125"/ 50"

Wheelbase Options

- ▶ 152 to 230" 4x2
- ▶ 173 to 256" 6x2, 6x4

Axle Configurations

- ▶ 4x2, 6x2, 6x4

Rear Axle

- ▶ SINGLE REAR AXLE (4x2)
 - Meritor: 23,000 lbs.
 - Dana Spicer: 23,000 lbs.
- ▶ TANDEM REAR AXLE (6x4)
 - Meritor: 40,000 - 46,000 lbs.
 - Dana Spicer: 40,000 - 46,000 lbs.

Front Axle

- Hendrickson: 12,350 - 14,000 lbs.
- Dana Spicer: 12,350 - 14,000 lbs.
- Meritor: 12,350 - 14,000 lbs.

Frames

- ▶ Heat-Treated Alloy Steel 120,000 PSI

Front Suspension

- ▶ Spring Monoleaf: 12,350 - 13,200 lbs.
- ▶ Parabolic Taperleaf: 12,350 - 14,000 lbs.

Rear Suspension

- ▶ AIR SINGLE
 - International®: 20,000 lbs.
- ▶ AIR TANDEM
 - International: 40,000 lbs.
 - Hendrickson: HAS 40,000 lbs - 46,000 lbs

Electrical System

- ▶ ALTERNATORS
 - Leece-Neville: 12 Volt, 160, 210, 240, 325* Amp
 - Delco Remy: 12 Volt, 165*, 200, 300* Amp
 - * brushless type alternator
- ▶ BATTERY SYSTEMS
 - Fleetrite®: 12 Volt 1980 - 7400 CCA
 - JCI: 12 Volt 2250 - 3000 CCA
 - Deka: 12 Volt 2920 CCA
 - Enersys Odyssey: 12 Volt 3450 - 9200 CCA

Exhaust System

- ▶ Single Canister After Treatment Device, Frame Mounted Right Side Under Cab
- ▶ Horizontal, Vertical, or Dual B Pillar Exhaust

Brakes

- ▶ Air Disc Brakes with Automatic Traction Control and Electronic Stability Control
- ▶ Air Drum Brakes with Automatic Traction Control and Electronic Stability Control

Integrated Powertrains

- ▶ International® S13 12.74L
 - 400 - 515 hp
 - 1,450 - 1,850 lb.-ft.
- ▶ International® T14
 - 14-speed automated manual transmission

Engines

- ▶ International® A26 12.4L
 - 400 - 515 hp
 - 1,450 - 1,850 lb.-ft.
- ▶ Cummins® X15 15L
 - 400 - 565 hp
 - 1,450 - 2,050 lb.-ft.

Transmissions

- ▶ Automated Manual Transmissions
 - Eaton Endurant: 11, 12 speed
 - Eaton Fuller UltraShift PLUS: 13, 18 speed
 - Eaton Fuller Advantage: 10 speed
- ▶ Manual Transmissions
 - Eaton Fuller: 10 speed
 - Fuller: 10, 13, 18 speed

Fuel Tanks

- ▶ 70 - 140 Gallon, Dual, Non-Polished or Polished Aluminum, Mounted Back of Cab
- ▶ 70 - 120 Gallon, Single, Non-Polished or Polished Aluminum, Mounted Back of Cab

Note: The information and conclusions contained herein are believed to be correct at time of publication, but do not necessarily apply to similar vehicles with different specifications or with production dates after the production of this publication. Vehicles with different specifications or later dates of production may yield different results. Vehicle specifications are subject to change without notice.

TAD16010 11/2023 ©2023 NAVISTAR Inc. All rights reserved. All marks are trademarks of their respective owners.